

Be more productive  
with easy-to-use, Wi-Fi\*  
and network\* ready,  
mono laser 4-in-1\*\*

**i-SENSYS**  
MF4730

**i-SENSYS**  
MF4750

**i-SENSYS**  
MF4780w

you can



Network\* and Wi-Fi\* ready, easy-to-use, compact mono  
laser multifunctional.

Wi-Fi\* and network\* ready, this mono laser multifunctional is freely  
accessed from around the home or office. Quick, easy-to-use  
and energy efficient, it is the ideal productivity booster.

#### Key features

- Compact, space-saving multifunctional printer, copier, scanner and fax\*\*
- Wi-Fi\* for wireless access around the home or office
- Quick 23ppm mono laser print and copy speed
- Simple operation with intuitive tilting control panel and large LCD screen
- Productivity-boosting, one-touch solution keys for managing scanning and copying workflows
- Built-in networking\* to share printing, scanning and faxing
- Quick First-Print offers fastest recovery time from sleep mode
- 35-sheet Automatic Document Feeder
- Save energy and cost with class-leading energy efficiency

#### What's in the box

Main unit, starter cartridge 728,  
power cord, telephone line cable,  
handset clamp, starter guide, wireless  
set-up guide\* and warranty card –  
with user software and manual CDs.

#### Dimensions (W x D x H)

390mm x 439mm x 360mm

#### Supported OS

Windows 7 / XP / Vista /  
Server 2003\* / Server 2008\* /  
Server 2008 R2\*

Mac OS Version 10.4.9 and up  
(Web distribution only)

Linux (Web distribution only)



PRINT



COPY



FAX\*\*



SCAN

\*MF4780w only \*\*MF4750 and MF4780w only.

**Canon**



# Specifications:

Machine type	Mono Laser All-in-One
Available functions	Print, Copy, Scan and Fax <sup>1</sup>
<b>PRINTER</b>	
Print speed	Up to 23ppm (A4)
Printing method	Monochrome laser beam printing
Print quality	Up to 1200 x 600 dpi with Automatic Image Refinement
Print resolution	600 x 600 dpi
First Print Out Time	6 seconds
Printer languages	UFRII-LT
Print margins	5mm – top and bottom, 5mm – left and right
Toner saver mode	Yes
<b>COPIER</b>	
Copy speed	Up to 23ppm (A4)
First Copy Output Time (FCOT)	Approx. 9 seconds or less
Copy resolution	Up to 600 x 600 dpi
Copy modes	Text, Text/Photo, Text/Photo+, Photo
Multiple copy	Up to 99 copies
Reduction / Enlargement	25-400% in 1% increments
Toner saver mode	Yes
Other features	Memory sort, 2 on 1, 4 on 1, ID Card Copy
<b>SCANNER</b>	
Type	Colour
Scan resolution	Optical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi
Colour scanning depth	24 bit / 24 bit (input / output)
Greyscales	256 levels
Compatibility	TWAIN, WIA
Max. scan width	216mm
<b>FAX<sup>1</sup></b>	
Modem speed	Super G3 33.6kbps
Receive mode	Fax Only, Manual, Answering, Fax / Tel Auto SW
Fax resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi
Fax memory	Up to 256 pages <sup>2</sup>
Speed dials	Max. 103 (including 3 one-touch dials)
Group dials / destinations	Max. 102 destinations
Sequential broadcast	Max. 113 locations
Memory backup	Unlimited
Other features	Dual Access, Remote RX, PC Fax (sending only), Fax Forwarding, DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports
Fax only applies to	MF4750dn and MF4780w
<b>MEDIA HANDLING</b>	
Scanner type	Flatbed and Automatic Document Feeder (ADF)
Paper input (Standard)	250-sheet tray, 1-sheet manual feed slot, 35-sheet ADF
Paper output	100-sheet
Media types	Plain paper, Heavy paper, Recycled paper, Transparency, Label, Envelope
Media sizes	Tray: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 210mm to Max. 216 x 356mm  Manual feed slot: A4, B5, A5, LGL, LTR, STMT, EXE, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, FLS, 16K, IndexCard, Envelope: COM10, Monarch, C5, DL, Custom sizes: Min. 76.2 x 127mm to Max. 216 x 356mm  ADF: A4, B5, A5, B6, LTR, LGL Min. 105 x 148mm to Max. 356 x 216mm
Media weights	Tray: 60 to 163g/m <sup>2</sup> Manual feed slot: 60 to 163g/m <sup>2</sup>

<b>INTERFACE &amp; SOFTWARE</b>	
Interface type	USB 2.0 Hi-speed, 10BASE-T / 100BASE-TX <sup>3</sup> , Wi-Fi 802.11b/g/n <sup>3</sup>
Operating System compatibility	Windows 7 / XP / Vista / Server 2003 <sup>3,4</sup> / Server 2008 <sup>3,4</sup> / Server 2008 R2 <sup>3,4</sup> / Mac OS X Version 10.4.9 and up <sup>5</sup> / Linux <sup>5,6</sup>
Software and printer management	Remote User Interface (RUI) <sup>3</sup> , Printer driver, Fax driver <sup>1</sup> , Scanner driver, MF Toolbox, AddressBookTool <sup>1</sup> , Presto! PageManager, SSID Tool <sup>3</sup>
<b>GENERAL FEATURES</b>	
Duty cycle	Max. 10,000 pages per month
Warm-up Time	Approx. 13.5 seconds from power on
Memory	128MB
Control panel	5 lines BW LCD
Dimensions with trays (W x D x H)	390mm x 439mm x 360mm
Installation space (W x D x H)	426mm x 555mm x 623mm
Weight	11.9kg
Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation)
Power Source	220-240V (±10%), 50/60Hz (±2Hz)
Power Consumption	Maximum: Approx. less than 1320W Active: Approx. less than 560W Stand by mode: Approx. 5W Sleep mode: Approx. 1.4W <sup>7</sup> Typical Electricity Consumption (TEC): 0.7kWh/week
Noise Levels	Sound Pressure: Active: 50dB(A) or less Standby: Inaudible
<b>CONSUMABLES</b>	
Cartridges	Cartridge 728 (2,100 pages <sup>8</sup> ) <sup>9</sup>
<b>ACCESSORIES / OPTIONS</b>	
Items	TELEPHONE KIT 6 <sup>1</sup>
Standard disclaimers. All specifications subject to change without notice.	
1) MF4750 and MF4780w only	
2) Based on ITU-T Standard Chart No. 1	
3) MF4780w only	
4) Network scanning not supported	
5) Web distribution only	
6) Linux support printing only	
7) When in wireless mode, consumption will be 2.4W	
8) Ships with 1,000 pages starter cartridge	
9) Based on ISO/IEC 19752	



Canon Electronics Inc  
canon.com

Canon Europe  
canon-europe.com

European Edition 0000  
© Canon Europa N.V.,  
2012 (0000)